

CR SERIES



EM POWER
LEADS
THE WAY



It is the ideal solution for crushing aggregates from small demolitions, excavations, or natural stones such as rocks, marble and tiles. Produced in two models, it requires only 380 V of electric power to operate.

STRENGTHS

- Easily transportable
- Control panel in safe position
- Easy and uncomplicated maintenance
- Crushing plates made of 18% manganese cast
- Three-phase electric engine inside the structure
- Loading hopper and support as standard

REALIZATION OF CUSTOMIZED PROJECTS



OPTIONAL

- Motor with different voltages and tensions (for non-EU countries)
- Customizable support
- Magnetic separator for metallic pieces
- Customizable loading hopper
- Conveyor belt for output material
- One or double deck vibrating screen

DATA SHEET		CR 400	CR 600
Mouth width	mm	400x200	600x300
Weight	Kg	1000	1500
Loading hopper	mm	1000x600	1300x800
Opening	mm	10/80	10/80
Voltage	V	380 V	380 V
Power	Kw	7,5	11
Dimensions	w x d x H	700 x 2010 x H 2260	910 x 2010 x H 2260



CRUSHING SIZE FROM 10 UP TO 80/10 mm STEP.
Weights and dimensions could vary without notice.



Canalization / Subsoil



Demolitions



Construction industry



Tunnel / Closed spaces



Agricultural / Forest maintenance



Recycling



Quarries / Mines



Streets